

BACKHOE

Model	BHM175		BHM195	
	Inch	Metric	Inch	Metric
Specification				
Tractor HP	25-30HP		30-45HP	
3-point Linkage	Cat-1		Cat-1	
Structure Weight	1060lb	480kg	1100lb	500kg
A Digging Depth(two foot flat bottom)	5.74'	1750mm	6.4'	1950mm
B Reach from center line of Swing pivot	8.53'	2600mm	9.51'	2900mm
C Loading Height(bucket at 60°)	5.64'	1720mm	6.03'	1840mm
D Transport Height(maximum)	6.03'	1840mm	6.75'	2060mm
E Extend Height	9.41'	2870mm	10.2'	3110mm
F Loading Reach(bucket at 60°)	3.11'	950mm	3.87'	1180mm
G Transport Overhang	3.54'	1080mm	3.64'	1110mm
H Undercut	2.4'	730mm	2.72'	830mm
I Bucket Rotation	180°		180°	
J Stabilizer Spread(up position)	4.3'	1310mm	4.3'	1310mm
K Stabilizer Spread(down position)	4.3'	2100mm	6.9'	2100mm
L Swing Arc	180°		180°	

Model	BHM225		BHM255	
	Inch	Metric	Inch	Metric
Specification				
Tractor HP	45-60HP		60-80HP	
3-point Linkage	CAT-1&2		Cat-1&2	
Structure Weight	1280lb	580kg	1370lb	620kg
A Digging Depth(two foot flat bottom)	7.38'	2250mm	8.36'	2550mm
B Reach from center line of Swing pivot	10.5'	3200mm	11.8'	3600mm
C Loading Height(bucket at 60°)	3.66'	1930mm	7.25'	2210mm
D Transport Height(maximum)	6.98'	2130mm	8.13'	2480mm
E Extend Height	10.62'	3240mm	11.77'	3590mm
F Loading Reach(bucket at 60°)	3.74'	1140mm	4.46'	1360mm
G Transport Overhang	4'	1220mm	4.16'	1270mm
H Undercut	1.54'	470mm	1.7'	520mm
I Bucket Rotation	180°		180°	
J Stabilizer Spread(up position)	4.3'	1310mm	4.3'	1310mm
K Stabilizer Spread(down position)	7.67'	2340m	7.67'	2340mm
L Swing Arc	180°		180°	